




OMM 323UQC

- 4-digit programmable projection
- Counter/frequency/clock/timer
- 0.1 Hz...50 kHz; UP/DW counter, IRC
- Digital filters, Tare, Linearization, Sum
- Size of DIN 48 x 24 mm
- Power supply 10...30 VDC / 24 VAC

Type OM 323UQC is an inexpensive 4-digit universal panel counter/frequency meter/timer/clock, designed for maximum usefulness and user comfort while maintaining its fair price.

The instrument is based on a microcontroller, which ensure good accuracy, stability and easy operation of the instrument.

UNIVERSAL COUNTER



OPERATION

The instrument is controlled by four buttons situated under the front panel. All programmable settings of the instrument may be performed in three adjusting modes:

LIGHT MENU is protected by optional number code and contains solely items necessary for instrument setting.

PROFI MENU is protected by optional number code and contains complete instrument setting.

USER MENU may contain arbitrary items from the programming menu (LIGHT/PROFI), which determine the right (see, change). Access w/o password.

Standard equipment is the OM Link interface, which together with operation program enables modification and filing of all instrument settings as well as performing firmware updates (with OML cable). The program is also designed for visualization and filing of measured values from more instruments.

All settings are stored in the EEPROM memory (settings hold even after the instrument is switched off).

STANDARD FUNCTIONS

PROGRAMMABLE PROJECTION

Input: NPN, PNP, on contact, IRC,

Setting: measuring mode counter/frequency/timer with adjustable calibration coefficient, time base and projection

Measuring modes: counter/frequency/UP-DW counter/frequency/counter for IRC

Measur. channels: A and B, from one measuring input two independent functions may be evaluated (counter/frequency)

Time base: 0.5/1/5/10 s

Projection: -999...9999 with fixed or floating DT format 10/24/60

FUNCTIONS

Linearization: non-linear signal is converted by a 25-point linear interpolation

Tare: designed to reset display upon non-zero input signal

Preset: initial nonzero value that is always read after resetting the device

Current value: one-off setting of the initial value

Summation: registration of figures upon shift operation

DIGITAL FILTERS

Exponential average: from 2...100 measurements

1/Fr.: filter to convert frequency to time

Rounding: setting the projection step for display

Input filter: passes the input signal up to 5...1 000 Hz

EXTERNAL CONTROL

Hold: display/instrument blocking

Lock: control keys blocking

Resetting: counter resetting

Start/Stop: timer/clock control

Sum: projection/resetting

Projection: counter/frequency measurement

TECHNICAL DATA

INPUT	
No. of inputs	1 The range is adjustable in the instrument menu
UQC Input	
on contact, TTL, NPN/PNP	
0...60 V, comparation levels are adjustable in the menu or automatic	
Input frequency	
0.1 Hz...50 kHz	SINGLE
0.1 Hz...20 kHz	UP/DW
0.1 Hz...20 kHz	UP-DW
0.1 Hz...20 kHz	QUADR., frequency
0.1 Hz...10 kHz	QUADR., counter, duty cycle 50%
Measuring mode	
SINGLE	counter/frequency
QUADR	counter/frequency for IRC sensors
UP/DW	UP/DW counter/frequency
	- measures on inputs A, B (direction) and can display numbers/frequency
UP - DW	UP - DW counter/frequency
	- measures on inputs A (UP), B (DW) and can display numbers/frequency
TIME	Timer
Time base	0.5/1/5/10 s
Multiplication constant	0.001...9999
Dividing constant	0.001...9999
Preset	0...9999
Input filter	0/5/40/100 / 1000 Hz
Functions	Preset Summation One time setting of the initial value

EXTERNAL INPUT

No. of inputs	1, on contact
Function	
No function assigned	
Measurement paused	
Control keys blocking	
Menu access blocking	
Display resetting	
Sum showing	
Counter/timer reset and preset	
Sum reset	
Switching counter/frequency display	

PROJECTION

Display	.999...9999, single color 7-segment LED
	99.99 hours / minutes
	23.59 hours / minutes
	59.59 minutes / seconds
	99.59 minutes / seconds
TIME	
TIME	
TIME	
TIME	
Digit height	9.1mm
Display color	red or green
Decimal point	adjustable - in menu
Brightness	adjustable or automatically controllable

INSTRUMENT SPECIFICATION

TC	50 ppm/°C
Accuracy	±0.05 % of value
Overload	2x
Functions	Tare, data backup, Preset, Summation
Digital filters	exponential average, rounding
Linearization	linear interpolation in 25 points setup only via OM Link
OM Link	company communication interface for operation, setting and update of instruments
Watch-dog	reset after 500 ms
Calibration	at 25°C and 40 % r.h.

POWER SUPPLY

Range	10...30 VDC / 24 VAC, ±10 %, PF ≥ 0.4, $I_{\text{sp}} < 45 \text{ A} / 1 \text{ ms}$, isolated
Consumption	< 1 W / 1.1 VA

MECHANIC PROPERTIES


Material	Noryl GFN2 SE1, incombustible UL 94 V-I, black
Dimensions	48 x 24 x 72 mm (w x h x d)
Panel cutout	43.5 x 21.5 mm (w x h)

OPERATING CONDITIONS

Connection	connector terminal blocks, section < 1.5 mm²
Stabilization period	within 5 minutes after switch-on
Working temperat.	-20°...60°C
Storage temperat.	-20°...85°C
Working humidity	< 95 % r.v., non condensing
Protection	IP42, front panel only
Construction	safety class I
El. safety	EN 61010-1, A2
Dielectric strength	2.5 kVAC for 1 min. between power supply and input
Insulation resist.*	for pollution degree II, measuring cat. III power supply > 300 V (PI)
EMC	EN 61326-1:2021, Industrial area
RoHS	EN IEC 63000:2018
Seismic qualification	IEC/IEEE 60980-344 Edition 1.0, 2020, par. 6, 9
Mechanical resistance	EN 60068-2-6 ed. 2:2008

* PI - Primary insulation, DI - Double insulation

CONNECTION



ORDER CODE

OMM 323UQC

- -

Power supply	10...30 VDC / 24 VAC	0
	10...30 VDC / 24 VAC, isolated	1
Display color	red	1
	green	2

Specification customized version, do not fill in

00

Basic configuration of the instrument is indicated in bold.