




OMX 212PM

- Input 0...2/5/10 V
0...5/20 mA, 4...20 mA, passive/active
- 2x Analog outputs, passive/active
- Quick configuration by DIP switch
- PC configurable via USB port
- Galvanic isolation 2.5 kVAC
- Simple instalation to DIN rail
- Power supply 10...30VDC, 24 VAC

DIGITAL ISOLATED TRASMITTERS



The OMX 200 model series are digital DIN rail mounted trasmitterss housed in an enclosure only 12.5 mm wide.

The OMX 212PM type is a simple single-channel isolator/splitter with a convenient setting of the input and output ranges either using a DIP switch on the side of the housing or the free OM Link SW from a PC.

You can also use this trasmitters as a splitter into 2 analogue outputs.

This device is based on a 32-bit processor and 24-bit $\Delta\Sigma$ ADC, which guarantees high accuracy and excellent stability.

OPERATION

The device can be configured either by DIP switch located on the side of the housing or by PC using the OM Link SW. The same SW can be used to edit and archive all device settings, as well as to perform firmware updates and customer calibration.

Tech-in process can be performed for the measuring range currently selected using the front panel buttons.

All settings are stored in the EEPROM memory (preserved even after power-off)

STANDARD FUNCTIONS*

PROGRAMMABLE INPUT

Measuring range: adjustable in menu

Standard setting: any input values can be assigned to Min and Max values of the analog output

Teach-in: any input values can be assigned to Min and Max values of the actual (unknown) input signal

Manual setting: the known Min and Max values of the input signal can be set manually and any analog output values can be assigned to each of them at the same time

ANALOG OUTPUT

Type: isolated, configurable with resolution of 10 000 parts, rate < 3.5 ms

Range: 0...10 V, 0...20 mA, 4...20 mA

FUNCTIONS

Linearization: non-linear signal is converted by a 50-point linear interpolation

Tare: designed to reset display upon non-zero input signal

Fixed tare: fixed preset tare

Simulation: test mode in which range, value and duration of the step can be set

Math functions: polynomial, inverse polynomial, logarithm, exponential, power, root

DIGITAL FILTERS

Floating / Exponential / Arithmetic average: from 2 to 100 measurements

Rounding: setting a „shorter” number for further signal processing

TECHNICAL DATA

INPUT	
No. of inputs	1 The range is selectable either by DIP switch or by OM Link free SW from PC
PM Range	0...5 mA < 200 mV 0...20 mA < 200 mV 4...20 mA < 200 mV ±2 V 1 MΩ ±5 V 1 MΩ ±10 V 1 MΩ

INSTRUMENT SPECIFICATION	
TC	50 ppm/°C
Accuracy	±0.1% of FS above accuracies apply for 20 meas./s
Rate	1...100 measurement/s
Latency	< 13 ms
Overload	10x (t < 30 ms), 2x
Functions	Teach-in, offset, tare, math. functions, simulation
Digital filters	exponential / floating / arithmetic average, rounding setup only via OM Link
Math functions	polynomial / inverse polynomial / logarithm / exponential / power / root setup only via OM Link
Linearization	linear interpolation in 100 points setup only via OM Link
OM Link	company communication interface for operation, setting and update of instruments (microUSB)
Watch-dog	reset after 500 ms
Calibration	at 25°C and 40% r.h.


ANALOG OUTPUTS	
No. of outputs	2
Type	isolated, adjustable with resolution of max. 10 000 points, type and range are selectable in menu
TC	15 ppm/°C
Accuracy	0.1% from FS
Rate	response to change of value < 3.5 ms
Ranges	0...10 / 0...0 V resistive load > 26 kΩ 0...20 / 0...0 mA comp. < 600 Ω/12 V 4...20 / 0...4 mA* comp. < 600 Ω/12 V active/passive* with error indication (< 3.6 mA)*
Error indication	at range 4...20 mA (ER-4-20) - A/D converter oversaturated - range exceeded by 20% (in both directions) - broken current loop 4...20 mA (< 3.6 mA)

EXCITATION	
Fixed	24 VDC / 35 mA, isolated only for 4...20 mA input

POWER SUPPLY	
Range	10...30 VDC / 24 AC, ±10%, PF ≥ 0.4, $I_{\text{sp}} < 40 \text{ A} / 1 \text{ ms}$, isolated Protection by fuse inside the device
Consumption	< 2.5 W / 2.4 VA
MECHANIC PROPERTIES	
Material	PA 66, incombustible UL 94 V-I, blue
Dimensions	12.5 x 99 x 114.5 mm (w x h x d)
Installation	on DIN rail, width 35 mm
OPERATING CONDITIONS	
Connection	connector terminal blocks, section < 2.5 mm²
Stabilization period	within 5 minutes after switch-on
Working temperat.	-20°...60°C
Storage temperat.	-20°...85°C
Working humidity	< 95% r.h., non condensing
Protection	IP20
Construction	safety class I
El. safety	EN 61010-1, A2
Dielectric strength	2.5 kVAC per 1 min test between supply and input 2.5 kVAC per 1 min test between supply and analog output 2.5 kVAC per 1 min test between analog outputs
Insulation resist.*	for pollution degree II, measuring cat. III power supply > 300 V (PI), 255 (DI) input, output > 300 V (PI)
EMC	EN 61326-1:2021, Industrial area
RoHS	EN IEC 63000:2018
Seismic qualification	IEC/IEEE 60980-344 Edition 1.0, 2020, par. 6, 9
Mechanical resistance	EN 60068-2-6 ed. 2:2008

* PI - Primary insulation, DI - Double insulation

CONNECTION



ORDER CODE

OMX 212PM

-

Specification customized version, do not fill in **00**